Diel srl
Via Retrone ,32/A
36077 Altavilla Vicentina (VI) - Italy
Tel. +39 0444 440977
mail: info@diel-ed.it - web: www.diel-ed.it

TECHNICAL DATASHEET

TERJT102FLXXX - TERJT112FLXXX

TERMOCOUPLE J TYPE ANSI/MC96,1

PICTURE

TECHNICAL DRAWING



TERMOCOUPLE

Materials	Iron positive pole, Copper-Nickel negative pole.
Isolation	Mylar glass fiber

TERMINAL

Terminal	T10 = PTFE	T11 = Welded non protected
Terminal diameter and lenght	T10 = Cylinder diameter 3,0 x 25 mm	//

CABLE

Cable type	Termocouple wire, PTFE isolation diam. 2,7, colour black (ANSI/MC 96,1)
Conductors (2 wires)	2x0,22 isolation silicon rubber, colours white (positive), red (negative)

PROBE

Probe lenght (XXX part of code)	XXX = lenght in decimeters
Finishing	Unseathing mm 30, Stripping mm 6
Temperature range	-60°C ÷ +220°C

TESTS

Insulating test between capsule and copper wire 2,5 KV AC for 60"
Dimensional and visual control 100%
Impedance at room temperature 100%
Functional control 100%

NOTES

DATE	REL
2018	1

The supplied data are indicatives and not bidding for us if not confirmed by written